

ARLYN SERIES 6200 PORTABLE BENCH SCALE

**HIGH ACCURACY
PORTABLE
BENCH
SCALES
BUILT
RUGGED
AND
EASY TO USE!**



EXPENSIVE SCALE FEATURES

(Features found on scales costing 3 to 5 times as much as Series 6200)

- HIGH ACCURACY** - High weight resolution to .0005 lbs.
 - Internal resolution to 1 part in 500,000
- EXTREMELY DURABLE** - Rugged heavy-duty construction
 - Stainless steel load cell
 - Large stainless weighing platform
 - Water resistant, gasketed, display housing
- ELIMINATES MAINTENANCE** - No moving parts
- EASY OPERATION** - Pushbutton functions for automatic and keyboard tare, tare functions with memory, net/gross, unit conversion with mode indicators
 - No set-up or dealer services required, automatic calibration functions

The Arlyn Series 6200 all-electronic portable bench scales feature the most rugged construction for survival and dependability in your industrial environment. They feature a large graphics LCD display, multiple alphanumeric memories and very high accuracy. All ARLYN electronic scales are shipped to you direct from the factory, and require none of the dealer services typically required on other digital scales. So instead of paying for a scale and a dealer, you pay only for the scale you need and nothing more. Which is why we've added just one inexpensive feature to the ARLYN Series 6200 Portable Bench Scales - the low price.

Weighs in lbs., grams, kg., ounces, troy, grains, etc.

Model number	620I	620X	620T	620C	620F
Capacity	3 lbs. 1.5 kgs.	10 lbs. 4.5 kgs.	25 lbs. 11 kgs.	100 lbs. 45 kgs.	150 lbs. 66 kgs.
Readability	.0001 lbs. 0.05 gram	.002 lbs. .001 kgs.	.005 lbs. .002 kgs.	.02 lbs. .01 kgs.	.05 lbs. .02 kgs.
Internal Res.	1 part in 500,000	1 part in 500,000	1 part in 500,000	1 part in 500,000	1 part in 500,000
Platform Dimensions	5" x 7"	12" x 16"	12" x 16"	12" x 16"	12" x 16"

ADDITIONAL SPECIFICATIONS

POWER REQUIREMENTS-
AC-117 VAC, 50/60 Hz. (220VAC Optional)
DC-Rechargeable Battery approx. 30 hours use, overnight recharge - optional

ACCURACY- 0.1% of full scale

DIMENSIONS- 15" x 17" x 3 1/2"
17 lb. shipping weight

TARE, ZERO RANGE- 100% of full scale

OPERATING TEMP.- 14°F to 104°F

DISPLAY SPEED- 0.4 seconds, adjustable

OVERLOAD CONDITION- Display warning message at 102% of scale capacity. Mechanical stops prevent damage to 150% of capacity.

ELECTRONICS-
32-bit microcomputer circuitry, self test feature. Electronics on 1-plug-in board for easy service.

DISPLAY- 1" high, easy-to-read graphics Liquid Crystal Display with status annunciators.

WEIGHING FEATURES- Adjustable filter constants, adjustable display update, automatic calibration

OPTIONS-

USB Computer port
RS-232 Computer port, adjustable rates
Time and Date output
Label, page and ticket printers
Automatic Setpoints for filling, etc.
Rechargeable Battery Pack



ARLYN SCALES www.arlynscales.com

CALL TOLL FREE 1-800-645-4301 - Fax# 516-593-4607

59 2ND St., E. Rockaway, NY 11518 (in NY 516-593-4465)