



# Arlyn Series D-6200 Portable Bench Scales

## DOUBLE PRECISION PORTABLE BENCH SCALES

www.arlynscales.com

The Arlyn Series D-6200 all-electronic **portable bench scales with double precision** feature the most rugged construction for survival and dependability in your industrial environment. The scale features *stainless steel load cells* and a *large stainless weighing platform*, giving the scale superior overload protection for years of trouble free use. Other features include easy installation, easy to read graphics LCD display, full numeric keypad, easy to use menu driven interface and large memory capacity. The indicator also offers Units Conversion, Net/Gross, Tare, Zero, and many other secondary functions. All ARLYN electronic scales are shipped to you direct from the factory, which allows the cost to be significantly lower than other equivalent scales.

Model	D-620X	D-620T	D-620L	D-620C	D-620F
Capacity	10lb (4.5kg)	25lb (11kg)	50lb (22kg)	100lb (45kg)	150lb (66kg)
Readability	0.001lb (0.0005kg)	0.002lb (0.001kg)	0.005lb (0.002kg)	0.01lb (0.005kg)	0.02lb (0.01kg)
Internal Resolution	1 part in 500,000	1 part in 500,000	1 part in 500,000	1 part in 500,000	1 part in 500,000
Readability Resolution	1 part in 10,000	1 part in 10,000	1 part in 10,000	1 part in 10,000	1 part in 10,000
Platform Dimensions	12" x 16"	12" x 16"	12" x 16"	12" x 16"	12" x 16"



\*Optional Swing arm available with MKE-5 indicators. Shown with optional UpScale Indicator w/ Remote Cable.

### FEATURES

**Very Accurate** - Internal resolution to 1:500,000, Nominal Resolution at 1:5000.

**Double Precision** - Readability Resolution at 1:10,000 with additional filtering.

**Cost Effective** - Includes features found on scales costing 5x more.

**Ultra Readability** - See Arlyn's exclusive SAW Ultra Precision Scales.

**Extremely Durable** - Rugged, heavy-duty construction. Water resistant, gasket, display housing.

**Swing Arm or Remote Cable** - Available in Swing Arm (MKE-5 only) or Remote Cable attachment.

**No Set Up** or dealer services required. Automatic calibration.

**Optional Touchscreen** - Available with Arlyn UpScale touchscreen indicator as shown above.\*

### ADDITIONAL SPECIFICATIONS

**Power Requirements** - 117/220VAC, 50/60 Hz.(incl. DC power adapter). Optional DC-Rechargeable battery approximately 20 hours use, overnight recharge (only available with MKE5 indicators)

**Accuracy** - 0.1% of full scale

**Shipping Dimensions** - 15" x 17" x 3.5", 17lb

**Tare, Zero Range** - 100% of full scale

**Operating Temp** - 14°F to 104°F

**Display** - 1" easy to read LCD with status annunciators

**Display Speed** - 0.5 seconds, adjustable

**Weighing Features** - Automatic calibration, eight unit conversions, net/gross, keyboard and digital tare with memory storage for tare and ID#s.

**UpScale Indicator Option** - 7" color touchscreen, visually driven user interface, user programmable extended accuracy parameters, multiple screen format choices, battery backup.

**Other Options** - RS-232, USB, Ethernet, Wi-Fi, 4-20mA, label and ticket printers, programmable setpoints for filling, mixing and monitoring, rechargeable battery, stainless platforms and indicator, ramps, parts counting.