



ArlynGuard-P Platform Scales

INTRINSICALLY SAFE PLATFORM SCALES

www.arlynscales.com

Take advantage of our **Explosion Proof Scales** that provide *intrinsic safety* at an affordable price. They feature a 32 bit RISC microprocessor incorporated on a single circuit board. Their extremely low power consumption provides long battery life from a single rechargeable C cell battery. The scale features stainless steel load cells giving the scale superior overload protection for years of trouble free use. Other features include easy installation, easy to read graphics LCD display, full numeric keypad, easy to use menu driven interface and large memory capacity. The indicator also offers Units Conversion, Net/Gross, Tare, Zero and many other secondary functions. Its housing is made from impact resistant nylon. The optional communications interface allows communication to non-hazardous areas, giving RS-232, analog and setpoint outputs.

Model	P5	P5-22x44	P10	P10-36x36	P10-SS
Capacity	500lb (220kg)		1000lb (440kg)		
Readability	0.1lb (0.05kg)	0.1lb (0.05kg)	0.2lb (0.1kg)		
Platform Dimensions	20" x 27"	22" x 44"	20" x 27"	36" x 36"	Stainless 20" x 27"



FEATURES

- Very Low Profile Platform** – 20"x27" aluminum plate (optional Stainless Steel) only 1 7/8" high.
- Very Accurate** - Internal resolution to 1 part in 500,000. Includes features found on scales costing 5x more...
- No Set Up** or dealer services required. Automatic calibration. Adjustable leveling legs.
- Optional Stainless Steel** – All models also available in **(SS)** stainless steel construction.
- Other Platform Sizes** – Also available in 30"x30" and 27"x60". *Other sizes available on request.*

ADDITIONAL SPECIFICATIONS

- Power Requirements** - Uses supplied 3800mah NiMH C cell battery. Two spare batteries are provided with recharger.
- Accuracy** - 0.1% of full scale
- Dimensions** - 20" x 27" x 1.8", 45lb shipping weight
- Tare, Zero Range** - 100% of full scale
- Operating Temp** - 14°F to 104°F
- Display** - 1" easy to read LCD with status annunciators
- Overload Condition** - Display warning message at 102% of scale capacity. Mechanical stops prevent damage to 150% of capacity.

- Display Speed** - 0.4 seconds, adjustable
- Electronics** - 32-bit microcomputer circuitry, self-test feature. All electronics on 1-plug board for easy service.
- Weighing Features** - Adjustable constants, automatic calibration, 100 alphanumeric memory locations for tare, ID#s, etc.
- Options** - Infrared communications interface allows communication to non-hazardous areas, giving RS-232, analog and setpoint outputs

INTRINSICALLY SAFE

Class I, II, III, Division 1, Groups A, B, C, D, E, F & G
 Class I, Zone 0, AEx ia IIC (T3 Ta=60C)
 Indoor Hazardous (Classified) Locations.
 Non-incendive for use in Class I, Division 2, Groups A, B, C and D.
 Suitable for use in Class II, Division 2, Groups F & G,
 Class III, Division 2 indoor Hazardous (Classified) Locations

APPROVALS

This ArlynGuard scale is equipped with one or more of:

- Model MKE-5-IS(-C) Digital Weight Indicator System
- Load Cell Models 620-300-IS, 620-100-IS, 620-50-IS, 620-25-IS, 620-10-IS, 520-10000L-IS, 520-5000L-IS, 520-5000IS, 520-2500-IS, 520-1250-IS, 320-500-IS and 320-250-IS

which are **Factory Mutual (FM) Approved components as per Approval Standard 3600, 3610, 3611 and 3810**